



TECHNICAL DATA SHEET

JD ALUMINUM Aluminum / Stainless Steel Cleaner

DESCRIPTION: A concentrated liquid aluminum and stainless steel cleaner, brightener, and conditioner for satin finish on over-the-road trucks and trailers.



Advantages:

Use on unpainted trucks, trailers, straight truck bodies. Restores original luster and shine.

Quickly removes oxidation, diesel smoke, dirt, and grease with minimum attack to aluminum.

Dead oxidized lettering paint is removed.

Specifications:

Physical Form	Clear Liquid
Color	Light Blue
Scent	Sharp Acid
Specific Gravity	1.29
Density	10.7 lbs. per gallon
Foam Test 1%	45mm
pH 1%	1.5
Acidity as H ₂ SO ₄ by Weight	39.44%
Acidity as HF by Weight	1.13%
Surfactant	2.3%
Total Activity	42.94%
DOT Classification	B

Directions:

USE EXTREME CAUTION! NOT TO BE USED BY AMATEURS. Protective clothing (including, but not necessarily limited to: apron, goggles, respirators, mask, face shield, gauntlet gloves, boots) is required when using this product.

DO NOT USE ON THE FOLLOWING SURFACES:

Bright aluminum or bright stainless steel, chrome, zinc, galvanized metal, tin, or magnesium. May produce etch to glass. To prevent, keep glass wet or cover the glass with a light coat of grease.

Dilute with water as follows:

Spray equipment: 1:50. Increase 1:40 in winter. Best results obtainable using hot water (140°F.)

Manual equipment: Use natural bristle brush. Do small area at a time. Thoroughly rinse off acid with clean water.

Apply by brushing or wet spraying **BOTTOM TO TOP** in panels or sections. **DO NOT** inhale or work in spray. **DO NOT** allow to dry on surface. Rinse the surface before it dries. Rinse any area that has been hit by overspray or mist. Overlay the edge of the old panel cleaned as you clean the new panel.

CAUTION

KEEP OUT OF REACH OF CHILDREN

Shipping Weight in Pounds:

Case 4 Plastic Gallons 46.9 pounds
5 Gallon Plastic Tighthead 58.0 pounds

