

MATERIAL SAFETY DATA SHEET

SECTION I - GENERAL INFORMATION

MRO Solutions L.L.C.
5645 West Howard Street
Niles, IL 60714
847/588-2480

SOLUTION 600 - HIGH TEMPERATURE RTV SILICONE SEALANT - RED

PROPER SHIPPING NAME (49CFR 172.101): NONE D.O.T. HAZARD CLASS (49CFR 172.101): NONE
D.O.T. HAZARD NAME (49CFR 172.101): NONE RCRA HAZARD CLASS (40CFR 261)(IF DISCARDED): NONE
D.O.T. ID NUMBER (49CFR 172.01): NONE E.P.A. PRIORITY POLLUTANTS (40CFR 122.53): NONE
NFPA - NATIONAL FIRE PROTECTION ASSOCIATION # 704
HEALTH (NFPA): 1 FLAMMABILITY (NFPA): 1 REACTIVITY (NFPA): 0
CAS NO: MIXTURE GENERIC DESCRIPTION: SILICONE

SECTION II - HAZARDOUS INGREDIENTS AS DEFINED IN 29 CFR 1910.1200

CAS NO.	INGREDIENT	WT%	EXPOSURE LIMITS
4253-34-3	METHYLTRIAACETOXYLANE	2	SEE COMMENTS BELOW
17689-77-9	ETHYLTRIAACETOXYLANE	2	SEE COMMENTS BELOW
7631-86-9	SILICA, AMORPHOUS	10	OSHA PEL: 6 MG/M ³ ACGIH TLV: TWA 10 MG/M ³ TOTAL DUST
1309-37-1	IRON OXIDE, RED Fe ₂ O ₃	1	OSHA PEL AS IRON: TWA 10 MG/M ³ TOTAL PARTICULATE, ACGIH TLV AS IRON: TWA 5 MG/M ³

COMMENTS: OBSERVE LIMITS FOR ACETIC ACID, FORMED DURING CURING ON EXPOSURE TO WATER OR HUMID AIR.
OSHA PEL: TWA 10 PPM; ACGIH TLV: TWA 10 PPM; STEL 15 PPM.

SECTION III EFFECTS OF OVEREXPOSURE

EYE: DIRECT CONTACT IRRITATES SLIGHTLY TO MODERATELY WITH REDNESS AND SWELLING.
SKIN: A SINGLE SHORT EXPOSURE (LESS THAN 24 HOURS) MAY IRRITATE. REPEATED PROLONGED CONTACT (24 TO 48 HOURS) MAY IRRITATE MODERATELY.
INHALATION: VAPOR OVEREXPOSURE MAY IRRITATE EYES, NOSE AND THROAT.
ORAL: SMALL AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS DURING USE, ETC., SHOULD NOT INJURE, SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.
COMMENTS: NO INJURY FROM SILICA DUST SHOULD OCCUR DURING REASONABLE USE. IF USE CREATES RESPIRABLE PARTICLES, SOME RESPIRATORY SYSTEM INJURY MAY OCCUR.
CURED SEALANT IS NONHAZARDOUS.
THE ABOVE LISTED POTENTIAL EFFECTS OF OVEREXPOSURE ARE BASED ON ACTUAL DATA, RESULTS OF STUDIES PERFORMED ON SIMILAR COMPOSITIONS, COMPONENT DATA AND/OR EXPERT REVIEW OF PRODUCT.
OVEREXPOSURE TO ANY CHEMICAL MAY RESULT IN ENHANCEMENT OF PRE-EXISTING ADVERSE MEDICAL CONDITIONS AND ALLERGIC REACTIONS.

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION
SKIN: WIPE OFF AND FLUSH WITH WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS.
INHALATION: REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF ILL EFFECTS PERSIST.
ORAL: NO FIRST AID SHOULD BE NEEDED.

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): NOT APPLICABLE AUTOIGNITION TEMP.: NOT DETERMINED
FLAMMABILITY LIMITS IN AIR (%): LOWER # NOT DETERMINED; UPPER # NOT DETERMINED
EXTINGUISHING MEDIA: WATER ___; WATER FOG X; CO₂ X; DRY CHEMICAL X; FOAM X; OTHER ___
SPECIAL FIREFIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE
COMMENTS: PRODUCT IS CONSIDERED A SOLID FOR DOT PURPOSES AND FLASHPOINT IS NOT APPLICABLE

SECTION VI - PHYSICAL DATA

BOILING POINT (AT 760 MM HG): NOT APPLICABLE SPECIFIC GRAVITY (AT 77°F/25°C): 1.03
MELTING POINT: NOT APPLICABLE SOLUBILITY IN WATER (%): LESS THAN 0.1
% VOLATILE BY WEIGHT: LESS THAN 5 EVAPORATION RATE: NOT APPLICABLE
VAPOR PRESSURE (AT 77°F/25°C): LESS THAN 5MM VAPOR DENSITY (AIR=1 AT 77°F/25°C): NOT APPLICABLE

ODOR: ACETIC ACID
PHYSICAL STATE: SOLID

FREEZE POINT: NOT APPLICABLE

SECTION VII - REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION, AIR OR MOISTURE CAUSES CURING AND THE LIBERATION OF ACETIC ACID VAPORS.

CONDITIONS TO AVOID: EXPOSURE TO AIR OR MOISTURE UNTIL READY TO USE.

HAZARDOUS DECOMPOSITION PRODUCTS: SILICON DIOXIDE, CARBON DIOXIDE AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION VIII - SPILL, LEAK, MAINTENANCE, REPAIR AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE PRODUCT AND CONTAIN FOR SALVAGE OR DISPOSAL.

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION - SAFETY GLASSES AS A MINIMUM

SKIN: WASHING AT MEALTIMES AND END OF SHIFT IS ADEQUATE. REMOVE CLOTHING AND SHOES AS SOON AS PRACTICAL AND CLEAN THOROUGHLY BEFORE REUSE. RUBBER OR PLASTIC GLOVES ARE RECOMMENDED.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR

SAMPLING DATA SHOW EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES.

WASTE DISPOSAL METHOD: ALL LOCAL, STATE AND FEDERAL REGULATIONS CONCERNING HEALTH AND POLLUTION SHOULD BE REVIEWED TO DETERMINE APPROVED DISPOSAL PROCEDURES.

D.O.T.(49CFR 171.8)/E.P.A.(40CFR 117) SPILL REPORTING INFORMATION

HAZARDOUS SUBSTANCES: NONE

CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE

REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

COMMENTS: PRODUCT CONTAINS NO INGREDIENT SUBJECT TO D.O.T. OR E.P.A. CERCLA/SARA ENVIRONMENTAL RELEASE REPORTING REGULATIONS. SEE SECTION XI FOR ADDITIONAL SARA COMPLIANCE INFORMATION.

SECTION IX - ROUTINE HANDLING PRECAUTIONS

PROTECTIVE EQUIPMENT:

EYES*: USE PROPER PROTECTION - SAFETY GLASSES AS A MINIMUM

SKIN: WASHING AT MEALTIMES AND END OF SHIFT IS ADEQUATE. REMOVE CLOTHING AND SHOES AS SOON AS PRACTICAL AND CLEAN THOROUGHLY BEFORE REUSE. RUBBER OR PLASTIC GLOVES ARE RECOMMENDED.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR

SAMPLING DATA SHOW EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES.

VENTILATION: LOCAL EXHAUST: RECOMMENDED - MECHANICAL (GENERAL): RECOMMENDED.

SUITABLE RESPIRATOR: ORGANIC VAPOR TYPE

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING; USE AT ELEVATED TEMPERATURES, OR AEROSOL SPRAY APPLICATIONS MAY REQUIRE ADDED PRECAUTIONS.

- GOOD PRACTICE REQUIRES THAT GROSS AMOUNTS OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.

COMMENTS: AVOID BREATHING VAPORS AND EYE AND SKIN CONTACT. USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY

SECTION X - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE BELOW 90°F/32°C. USE REASONABLE CARE AND CAUTION. KEEP CONTAINER CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS: PRODUCT FORMS ACETIC ACID WHEN EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL ACETIC ACID EXPOSURE WITHIN 10 PPM (CURRENT TLV) OR USE RESPIRATORY PROTECTION.

COMMENTS: TRACES OF FORMALDEHYDE (CARCINOGEN) MAY FORM IF HEATED IN AIR ABOVE 300°F/149°C. PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURE WITHIN INHALATION GUIDELINES WHEN HANDLING AT ELEVATED TEMPERATURES. REVIEW THE OSHA FORMALDEHYDE REGULATION FOR DETAIL INFORMATION ON SAFE HANDLING REQUIREMENTS.

SECTION XI - COMMENTS

ADDITIONAL SARA REGULATORY COMPLIANCE INFORMATION:

SEC. 312 HAZARD CLASS: IMMEDIATE

SEC. 313 NOTIFICATION: NOT APPLICABLE n EITHER NONE PRESENT OR NONE PRESENT IN REGULATED QUANTITIES.

SUPPLEMENTAL STATE COMPLIANCE INFORMATION:

PENNSYLVANIA:	10%	7631-86-9	SILICA, AMORPHOUS
		70131-67-8	POLYDIMETHYLSILOXANE, HYDROXY TERMINATED
MASSACHUSETTS:	10%	7631-86-9	SILICA, AMORPHOUS
NEW JERSEY	10%	7631-86-9	SILICA, AMORPHOUS, FUMED #1655
		4253-34-3	METHYLTRACETOXSILANE
		17689-77-9	ETHYLTRACETOXSILANE
		70131-67-8	POLYDIMETHYLSILOXANE, HYDROXY TERMINATE
<hr/>			
		63148-62-9	POLYDIMETHYLSILOXANE

The data contained herein is based upon information that mro Solutions L.L.C. believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.