CITGO COMPRESSOR OIL 35LP

Date 1/09

DESCRIPTION: A high-quality non-foaming, non-detergent compressor cylinder lubricant engineered for the requirements of air and gas compressors and older gas engines that utilize activated clay filtration.

CITGO Compressor Oil 35LP employs high VI paraffinic base stocks with additives to inhibit oxidation, rust and corrosion, and possesses additional demulsibility characteristics.

QUALITIES:

- High viscosity index provides superior viscosity-temperature characteristics.
- Low pour point for cold climate operations.
- Low carbon forming tendencies together with oxidation resistance minimizes exhaust valve deposits.

APPLICATIONS: **CITGO Compressor Oil 35LP** is recommended for cylinder lubrication of reciprocating air and gas compressors.

TYPICAL PROPERTIES:

CITGO COMPRESSOR OIL 35LP	
Material Code	633746001
Gravity, ASTM D 4052, °API	29.2
Density, lb/gal	7.284
Flash Point, ASTM D 92, °F (°C)	554 (290)
Viscosity, ASTM D 445, cSt at 40°C	115
cSt at 100°C	12.3
ASTM D 2161, SUS at 100°F	600
SUS at 210°F	69
Viscosity Index, ASTM D 2270	97
Pour Point, ASTM D 97, °F (°C)	-17 (-27)
Color, ASTM D 1500	L2.0
Total Acid No. mgKOH/g, ASTM D 664	0.1
Foam Test, Seq. I, ml, ASTM D 892	0-0
Seq. II, ml, ASTM D 892	0-0
Seq. III, ml, ASTM D 892	0-0
RPVOT, Oxidation, ASTM D 2272, minutes	320