

CECOR fresh Coolant Dispensers distribute clean coolant to machine tools. Use plant air supply for the DA5 series. Use single phase electric for DE10 series. Gravity Dispenser DX-110PL provides an easy way to dispense coolant and oil without a power source.

- **DA5 and DE10 available in 90, 140 and 175 gallon capacity. DX-110PL has a 110 gallon capacity.**
- **Air unit discharge rate to 25 gallons per minute, electric unit discharge rate to 23 gallons per minute.**
- **Loads through fill-hatch or suction pump-in.**
- **Automatic Overfill Protection.**
- **Safe, easy one-person handling.**

Paired with a CECOR Coolant Sumpcleaner becomes a two-unit system for collection and delivery cycle.



DE10-175PT Coolant Dispenser

Caution: Machines must not be used for flammable fluids (fuels, paints, solvents, etc.) Avoid use in extra-high temperature or spark-hazard environments (ovens, welding areas, etc.)

CECOR Gravity Dispenser DX-110PL

Gravity Dispenser DX-110PL is a low-cost option for dispensing coolant and oil without a power source. Plastic polyethylene tank empties through a plastic hose fitted with a full flow nozzle or by a faucet drain located in the base.

- Liquid level visible through translucent tank.
- Capacity: 110 gallons
- Gallon markings on tank.
- Mounted on two swivel and two rigid 8" casters with poly tires.
- Channel construction for secure fork lift entry.
- Shipping weight: 462 lbs.



DX-110PL

Powered Coolant Dispensers

Tank Size: 90, 140 and 175 gallon capacity.

Pump: **(Electric Unit)-DE10**
 1 HP Electric Motor driving rotary vane-type air pump
 Volts 115
 Amps 13.4
 Hertz 60
 Phase 1

15' electric power cord.

(Air Unit)-DA5
 Air operated vacuum/pressure unit creates regulated light pressure for easy flow discharge.

20' oil resistant air supply hose.

Requirements: 1/2" air service with line pressure of 75 to 120 PSI (pounds per square inch).

Pumping Rate: 25 gallons per minute - Air Series.
 23 gallons per minute - Electric Series.

Discharge: 53 - 80 CFM (cubic feet per minute).

Tank: Heavy gage steel with push handle and tow bar. Convenient liquid level indicator. 6" fill hatch. Bottom drain plug.

Transport: Mounted on two 12" x 3" poly wheels and one 8" x 3" poly caster. Durable poly wheels are resistant to oil and chips. Roller bearing wheels for easy one-person handling.

Spill Prevention: Automatic overfill control. All discharge ports valved.

Hose: 1-1/4" I.D. x 16' oil-resistant PVC dispensing hose with full-flow shut-off nozzle.

Model Number	Tank Size	Transport	Wheels	Dimensions	Shipping Weight
DE10-90PT	90 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	62" long 30" wide 48" high	580 lbs.
DE10-140PT	140 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	62" long 34" wide 54" high	620 lbs.
DE10-175PT	175 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	74" long 34" wide 54" high	735 lbs.
DA5-90PT	90 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	62" long 30" wide 51" high	470 lbs.
DA5-140PT	140 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	62" long 34" wide 57" high	510 lbs.
DA5-175PT	175 gallons	PT Base for push or tow transport	Two 12" x 3" poly wheels and one 8" x 3" poly caster	74" long 34" wide 57" high	625 lbs.
DX-110PL	110 gallons	Push bar, front end bumpers	Two swivel and two rigid 8" casters with poly tires.	54" long 31" wide 52" high	462 lbs.

NOTE: Engineering specifications subject to change without notice.