



**Product #:** SUMP SHARK

**Product Name:** Sumpcleaner/Filter: Air-Operated

**Description:** Suction rates to 70 gallons per minute removes dirty coolant. Filters out solids. Provides low initial cost, low operating cost. Complete with a 1-1/2" x 16' suction/discharge hose fitted with quick disconnect couplers and straight nozzle.

**Pricing Information:**

**Unit Price:** QUOTE

**Package Type:** Each

**Units Per** 1

**Package:**

**Product Details:**

**Tank Size(gallons):** 60

**Pump:** Air operated venturi

**Requirements:** Requires air runs (headers) 3/4" to larger and vertical drops of 1/2" or more with line pressure of 75 to 120 psi (53 to 80 CFM)

**Pumping Rate:** Up to 70 gallons per minute

**Suction Lift:** 360" water or 26" Hg (Mercury)

**Pressure:** 6 PSI with safety backup valve.

**Discharge:**

**Filter:** 1 cu.ft. standard; F23 (2.3 cu.ft) optional

**Spill Prevention:** Automatic overflow protection. All discharge ports are valved.

**Hose:** 1-1/2" I.D. x 16' oil-resistant PVC suction/discharge hose including quick-disconnect couplers and suction tools.

**Cleaning Tools:** Straight nozzle

**Transport Mode:** Push/Lift. Easy manual maneuvering with fork pockets for forklift transport.

**Wheels:** Two 8" x 2" phenolic wheels and one 6" x 2" phenolic caster.

**Drain Port:** 2-1/4" drain port.

**Dimensions:** 36" long x 33" wide x 54" high

**Shipping Weight(lbs.):** 410