



GLOC SOLV PLUS

DESCRIPTION

Product Data

GLOC SOLV PLUS is a solvent machine and parts cleaner to be used as received. This product is safe for use on all metals. **GLOC SOLV PLUS** is formulated from high purity ingredients to promote superior cleaning and operator acceptance.

KEY PERFORMANCE BENEFITS

Safe to use as directed on all metalworking aluminum and copper
Phosphate and Nitrite Free
Non-Corrosive

TYPICAL PRODUCT APPLICATIONS

GLOC SOLV PLUS to be used on parts that are painted or coated should be tested to be certain that this material does not remove the coating. To use simply submerge parts into sump, dip basket, etc. This will effectively clean a surface of oil, grease and contaminants. Ambient temperatures to 120°F are recommended for best results. Once parts are removed they may be allowed to air dry at ambient conditions or forced air dried. This should be used before introducing new lubricants.

METALWORKING FLUIDS * AIRCRAFT * INDUSTRIAL * AUTOMOTIVE

GREAT LAKES OIL COMPANY, INC.

1657 Mentor Ave. Suite 1A
Painesville, Ohio 44077
Phone# 1.440.352.9050 Fax # 1.440.639.8010
USA Toll Free 1(800).352.9050
Web page: www.greatlakesoil.com
E-mail: glocsales@greatlakesoil.com

TYPICAL PHYSICAL AND CHEMICAL CHARACTERISTICS

| | |
|------------------------|---------------|
| Color | Colorless |
| Appearance | Clear, Liquid |
| Odor | Orange Peels |
| Flash Point, PMCC | 142°F |
| Density (LBS/GAL) | 6.348 |
| Viscosity at 40 °C cSt | 2.70 |
| Viscosity at 40 °C SUS | 35.0 |
| A.P.I. Gravity @ 60°F | 54.2 |
| Dilution | Neat |
| VOC Content #/gal | 6.348 |

The outstanding physical characteristics of this product coupled with the cost / performance ratio justify looking at replacing your present *solvent cleaner*.

Storage/Handling/Disposability

No health or safety hazards exist when **GLOC Solv Plus** metalworking fluids are stored, used and disposed of in accordance with instructions given on the Material Safety Data Sheet for this product.