



CLARION® GREEN FORM OIL

Date 1/09

DESCRIPTION: Clarion Green Form Oil is a heavy duty, compounded release agent for metal or wooden forms used in severe service concrete work.

QUALITIES: Clarion Green Form Oil is formulated with a Food Grade White Mineral Oil and complimentary additives to produce an environmentally friendly product. It is inherently biodegradable, non-toxic to aquatic life, will not leave a sheen on the water, and will meet California Standards for VOC.

Clarion Green Form Oil is essentially water white in color to prevent staining of the concrete pour, and gives improved form and mold separations for use in difficult or complex concrete pours.

Clarion Green Form Oil is compounded with a release agent to enhance corrosion protection, and an oiliness agent for ease of spreading, and will displace water from metal surfaces.

Clarion Green Form Oil can be applied by spray, brush, swab, or dipping, and is foam resistant to ensure the integrity of the protective film during pressure spray application.

APPLICATIONS: Clarion Green Form Oil is recommended for lubricating metal or wooden concrete forms used in environmentally sensitive areas.

Clarion Green Form Oil Can be applied at nominal operating conditions without dilution or heating.

TYPICAL PROPERTIES:

CLARION® GREEN FORM OIL

ISO VIS Grade	15
Material Code	643230009
Gravity, ASTM D 4052, °API	34.0
Density, lbs/gallon	7.115
Flash Point, COC, ASTM D 92, °C (°F)	182 (360)
Pour Point, ASTM D 97, °C (°F)	-26 (-15)
Color, ASTM D 1500	1.0
Viscosity, ASTM D 445, cSt at 40°C	13.00
Volatile Organic Compounds, ASTM D 2369, Neat Solution	4.55%
Volatile Organic Compounds, Grams/Liter, Neat Solution ¹	<50

¹ Results are based on a single determination.